

Palub 產品資料表

No.	產品	色相	酸價 (mgKOH/g)	40°C 運動黏度 (mm ² /s)	100°C 運動黏度 (mm ² /s)	黏度指數	開杯閃火點 (°C)	傾點 (°C)	應用													單位包裝 (Kg/Drum)				
									礦油	金屬加工液	紡織潤滑油	液壓油	二行程機油	四行程機油	液壓/傳動系統	渦輪機油	船用潤滑油	空壓機油	潤滑脂	鏈條油	潤滑油添加劑		熱機油	鑿型器油	食品級認證 NSF HX-1	
單酯																										
1	Palub 8830	60	0.70	4.6	1.8	--	180	8	●	●															180	
2	Palub 8136	20	0.05	5.1	1.8	150	180	-36			●															175
3	Palub 8101	20	0.05	6.4	2.2	193	195	21	●																	175
4	Palub 8110P	100	0.50	8.2	2.6	180	220	-27		●		●														180
5	Palub 8112	20	0.03	8.4	2.6	165	208	0			●	●														175
6	Palub 8103	20	0.05	9.2	2.8	166	210	4	●		●															180
7	Palub 8166PF	G2	0.30	15	4.1	186	256	-27			●															180
8	Palub 8106	30	0.10	18	4.4	168	235	6		●	●															180
9	Palub 8148	50	0.05	26	5.5	162	255	-36							●	●										170
雙酯																										
10	Palub 8218	15	0.05	12	3.2	156	225	<-50						●	●	●										190
11	Palub 8234H	25	0.05	28	5.5	138	244	<-54						●	●			●								190
甘油酯																										
12	Palub 8313	G2	0.80	38	8.3	200	300	-18		●		●												●		190
13	Palub 8302	3 / 0.5	0.50	51	8.5	142	245	0	●	●																190
14	Palub 8303P	150	0.50	136	12	73	210	-3						●										●		190
多元醇酯																										
15	Palub 8406	50	0.05	20	4.4	140	260	-48						●	●	●									●	190
16	Palub 8407	30	0.05	20	4.5	143	268	-50						●	●	●									●	190
17	Palub 8439E	150	0.03	24	4.9	138	250	<-57						●	●	●	●							●	●	200
18	Palub 8236P	G1	0.50	24	6.0	215	290	-21						●												180
19	Palub 8431	100	0.05	30	6.0	148	280	-6			●				●											190
20	Palub 8409	100	0.05	31	6.1	148	282	9			●				●											190
21	Palub 8410	G0.2	0.02	44	6.2	85	250	0										●	●							180
22	Palub 8429	G0.5	1.30	40	7.8	172	300	3		●	●															190
23	Palub 8492	30	0.01	68	8.3	88	264	-39										●	●							190
24	Palub 8427	30	0.03	68	8.8	102	270	-39											●	●						200
25	Palub 8404P	4 / 1	0.50	46	9.6	190	310	-42		●		●								●						190
26	Palub 8405P	4 / 1	0.50	63	12	188	315	-21				●								●						190
27	Palub 8498	80	0.05	103	13	122	298	-42																●		190
28	Palub 8426	G5	0.30	105	15	150	280	-27				●			●					●						185
29	Palub 8416	G1	0.50	142	18	140	306	-36					●		●					●	●					190
30	Palub 8499	80	0.05	219	19	101	294	-30												●	●					190
31	Palub 8475	80	0.05	320	24	93	300	-27												●	●					190
32	Palub 8457	50	0.02	390	26	89	296	-18												●	●				●	200
芳香酯																										
33	Palub 8835	20	0.05	3.9	1.3	--	156	<-50		●																190
34	Palub 8433X	50	0.05	52	8.1	126	278	-48												●				●	●	200
35	Palub 8432	25	0.05	88	9.6	82	255	-45												●		●		●		200
36	Palub 8451	25	0.05	111	12	75	265	-45												●		●		●		200
37	Palub 8461C	30	0.05	135	13	84	280	-36												●	●					200
38	Palub 8434H	50	0.05	322	21	74	276	-33												●	●			●		185
複合酯/聚酯																										
39	Palub 8511	200	0.20	46	8.0	140	260	-45							●					●	●					190
40	Palub 8446	G4	0.10	400	40	150	310	-39																		190
41	Palub 8516	200	0.20	320	40	150	280	-33				●								●	●					190
42	Palub 8467	G4	0.10	1700	125	175	310	-21												●		●				190
43	Palub 8646	G7	0.30	5000	310	200	318	-24																●		190
44	Palub 8466	G5	0.10	47000	2000	278	312	--																●		180

